

# TECHNICAL DATA

## PITCH DIAMETER LIMITS

For Internal Screw Thread Classes and Tap Recommendations



Size	Threads Per Inch		Basic Pitch Diameter	Unified Classes of Threads				American National Classes of Threads				ISO Metric Class of Threads				
	NC UNC	NF UNF		Class 2B for General Applications		Class 3B for Closer Fits		Class 2		Class 3		Class for 6H Commercial Threads				
			All Classes Minimum	Pitch Diam. Limits Maximum	Rec.* Taps	Pitch Diam. Limits Maximum	Rec.* Taps	Pitch Diam. Limits Maximum	Rec.* Taps	Pitch Diam. Limits Maximum	Rec.* Taps	Size mm	Pitch mm	Pitch Diameter Limits (in)		Rec. Taps
														Min.**	Max.	
0		80	0.0519	0.0542	H2	0.0536	H1	0.0536	H1	0.0532	H1	M1.6	0.35	0.0541	0.0574	D3
1	64	72	0.0629	0.0655	H2	0.0648	H1	0.0648	H1	0.0643	H1	M2	0.4	0.0686	0.072	D3
			0.064	0.0665	H2	0.0659	H1	0.0658	H1	0.0653	H1	M2.5	0.45	0.087	0.0906	D3
2	56		0.0744	0.0772	H2	0.0765	H1	0.0764	H1	0.0759	H1	M3	0.5	0.1054	0.1092	D3
		64	0.0759	0.0786	H2	0.0779	H1	0.0778	H1	0.0773	H1	M3.5	0.6	0.1225	0.1268	D4
3	48		0.0855	0.0855	H2	0.0877	H1	0.0877	H1	0.0871	H1	M4	0.7	0.1396	0.1442	D4
		56	0.0874	0.0902	H2	0.0895	H1	0.0894	H1	0.0889	H1	M5	0.8	0.1764	0.1812	D4
4	40		0.0958	0.0991	H2	0.0982	H2	0.0982	H2	0.0975	H1	M6	1	0.2107	0.2165	D5
		48	0.0985	0.1016	H2	0.1008	H1	0.1007	H1	0.1001	H1	M8	1.25	0.283	0.2892	D5
5	40		0.1088	0.1121	H2	0.1113	H2	0.1112	H2	0.1105	H1	M10	1.5	0.3554	0.3624	D6
		44	0.1102	0.1134	H2	0.1126	H1	0.1125	H1	0.1118	H1	M12	1.75	0.4277	0.4355	D6
6	32		0.1177	0.1214	H3	0.1204	H2	0.1204	H2	0.1196	H1	M14	2	0.5001	0.5083	D7
		40	0.1218	0.1252	H2	0.1243	H2	0.1242	H2	0.1235	H1	M16	2	0.5788	0.5871	D7
8	32		0.1437	0.1475	H3	0.1465	H2	0.1464	H2	0.1456	H1	M20	2.5	0.7235	0.7322	D7
		36	0.146	0.1496	H2	0.1487	H2	0.1485	H2	0.1478	H1	M24	3	0.8682	0.8785	D8
10	24		0.1629	0.1672	H3	0.1661	H3	0.1662	H3	0.1653	H1	M30	3.5	1.0917	1.1026	D9
		32	0.1697	0.1736	H3	0.1726	H2	0.1724	H2	0.1716	H1	M36	4	1.3151	1.3268	D9
12	24		0.1889	0.1933	H3	0.1922	H3	0.1922	H3	0.1913	H1	*Basic Pitch Diameter: NOTE: P.D. Limits for recommended taps: D3 = Basic Plus .0009" to Basic Plus .0015" D4 = Basic Plus .0012" to Basic Plus .002" D5 = Basic Plus .0015" to Basic Plus .0025" D6 = Basic Plus .0018" to Basic Plus .003" D7 = Basic Plus .0019" to Basic Plus .0035" D8 = Basic Plus .0024" to Basic Plus .004" D9 = Basic Plus .0025" to Basic Plus .0045"				
		28	0.1928	0.197	H3	0.1959	H3	0.1959	H3	0.195	H1					
1/4	20		0.2175	0.2224	H5	0.2211	H3	0.2211	H3	0.2201	H2	The above recommended taps normally produce the class of thread indicated in average materials when used with reasonable care. However, if the tap specified does not give a satisfactory gage fit in the work, a choice of some other limit tap may be necessary.				
		28	0.2268	0.2311	H4	0.23	H3	0.2299	H3	0.229	H1					
5/16	18		0.2764	0.2817	H5	0.2803	H3	0.2805	H3	0.2794	H2	** Sizes through 1" diameter: H1 = Basic to Basic Plus .0005" H2 = Basic Plus .0005" to Basic Plus .0010" H3 = Basic Plus .0010" to Basic Plus .0015" H4 = Basic Plus .0015" to Basic Plus .0020" H5 = Basic Plus .0020" to Basic Plus .0025" H6 = Basic Plus .0025" to Basic Plus .0030" H7 = Basic Plus .0030" to Basic Plus .0035" H8 = Basic Plus .0035" to Basic Plus .0040" H9 = Basic Plus .0040" to Basic Plus .0045" H10 = Basic Plus .0045" to Basic Plus .0050" H11 = Basic Plus .0050" to Basic Plus .0055"				
		24	0.2854	0.2902	H4	0.289	H3	0.2887	H3	0.2878	H1					
3/8	16		0.3344	0.3401	H5	0.3387	H3	0.3389	H3	0.3376	H2	Sizes larger than 1" diameter thru 1-1/2": H4 = Basic Plus .0010" to Basic Plus .0020"				
		24	0.3479	0.3528	H4	0.3516	H3	0.3512	H3	0.3503	H1					
7/16	14		0.3911	0.3972	H5	0.3957	H3	0.396	H5	0.3947	H3					
		20	0.405	0.4104	H5	0.4091	H3	0.4086	H3	0.4076	H1					
1/2	13		0.45	0.4565	H5	0.4548	H3	0.4552	H5	0.4537	H3					
		20	0.4675	0.4731	H5	0.4717	H3	0.4711	H3	0.4701	H1					
9/16	12		0.5084	0.5152	H5	0.5135	H3	0.514	H5	0.5124	H3					
		18	0.5264	0.5323	H5	0.5308	H3	0.5305	H3	0.5294	H2					
5/8	11		0.566	0.5732	H5	0.5714	H3	0.5719	H5	0.5702	H3					
		18	0.5889	0.5949	H5	0.5934	H3	0.593	H3	0.5919	H2					
3/4	10		0.685	0.6927	H5	0.6907	H5	0.6914	H5	0.6895	H3					
		16	0.7094	0.7159	H5	0.7143	H3	0.7139	H3	0.7126	H2					
7/8	9		0.8028	0.811	H6	0.8089	H4	0.8098	H6	0.8077	H4					
		14	0.8286	0.8356	H4	0.8339	H4	0.8335	H4	0.8322	H2					
1	8		0.9188	0.9276	H4	0.9254	H4	0.9264	H4	0.9242	H4					
		12	0.9459	0.9535	H4	0.9516	H4	0.9515	H4	0.9499	H4					
		14NS	0.9536	0.9609	H4	0.959	H4	0.9585	H4	0.9572	H4					
1-1/8	7		1.0322	1.0416	H4	1.0393	H4	1.0407	H4	1.0381	H4					
		12	1.0709	1.0787	H4	1.0768	H4	1.0765	H4	1.0749	H4					
1-1/4	7		1.1572	1.1668	H4	1.1644	H4	1.1657	H4	1.1631	H4					
		12	1.1959	1.2039	H4	1.2019	H4	1.2015	H4	1.1999	H4					
1-3/8	6		1.2667	1.2771	H4	1.2745	H4	1.2768	H4	1.2738	H4					
		12	1.3209	1.3291	H4	1.372	H4	1.3265	H4	1.3249	H4					
1-1/2	6		1.3917	1.4022	H4	1.3996	H4	1.4018	H4	1.3988	H4					
		12	1.4459	1.4542	H4	1.4522	H4	1.4515	H4	0.1450	H4					